



Safety Data Sheet

Issue date 17-Jul-2018

Revision date 05-Aug-2026

Revision Number 7

1. IDENTIFICATION

Product identification

Product identifier Kent® Acrysol Auto Body Degreaser

Other means of identification P60170

Recommended use Cleaner

Restrictions on use For industrial use only,
KEEP OUT OF REACH OF CHILDREN

Supplier

Corporate Headquarters:
Kent Automotive
8770 W. Bryn Mawr Ave.- Suite 600
Chicago, IL 60631
(888)-937-5368

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

Website www.lawsonproducts.com

2. HAZARD(S) IDENTIFICATION

Hazard Classification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2025 and Mexico (NOM-018-STPS-2015) GHS Regulations.

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Aerosols	Category 1
Gases under pressure	Liquefied Gas

Symbol



Signal word	DANGER
Hazard statements	H222 - Extremely flammable aerosol H280 - Contains gas under pressure; may explode if heated H315 - Causes skin irritation H336 - May cause drowsiness or dizziness H373 - May cause damage to organs through prolonged or repeated exposure H304 - May be fatal if swallowed and enters airways
Precautionary statements	
General	P103 - Read label before use. P102 - Keep out of reach of children P101 - If medical advice is needed, have product container or label at hand
Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source P251 - Do not pierce or burn, even after use P264 - Wash hands thoroughly after handling P280 - Wear protective gloves P260 - Do not breathe dust, fumes, gas, mist, vapors, spray P271 - Use only outdoors or in a well-ventilated area
Response	
Skin	P302 + P352 - IF ON SKIN: Wash with plenty of soap and water P332 + P313 - If skin irritation occurs: Get medical attention P362 - Take off contaminated clothing and wash before reuse
Inhalation	P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell
Ingestion	P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor P331 - Do NOT induce vomiting
Storage	P405 - Store locked up P410 - Protect from sunlight P412 - Do not expose to temperatures exceeding 50 °C/122 °F P403 - Store in a well-ventilated place
Disposal	P501 -Dispose of contents and container in accordance with local, regional, and federal regulations.
Hazard(s) Not Otherwise Classified (HNOC)	Not available.
Physical Hazards Not Otherwise Classified (PHNOC)	Not available.
Unknown acute toxicity	No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2025 and Mexico (NOM-018-STPS-2015) GHS Regulations.

Composition Mixture.

Chemical name	Syns/Common Name	CAS-No	Weight %
Light Aliphatic Hydrocarbon Solvent	Light Aliphatic Hydrocarbon Solvent	64742-49-0	25-35
Distillates, petroleum, light distillate	Distillates, petroleum, light distillate	68410-97-9	25-35
Propane	Propane	68476-86-8	20-30
Xylenes (o-, m-, p- isomers)	Xylenes (o-, m-, p- isomers)	1330-20-7	10-20
Ethyl benzene	Ethyl benzene	100-41-4	1-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or environment and hence require reporting in this section

4. FIRST-AID MEASURES

Necessary first-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	Rinse mouth with water. Do not induce vomiting without medical advice. Keep head below hips if vomiting occurs. Seek medical attention immediately. Aspiration hazard if swallowed. May enter lungs and cause damage. Never give anything by mouth to an unconscious person.
Skin contact	Wash affected areas with large amounts of soap and water for 15 minutes. Remove contaminated clothing and shoes. Seek medical attention if irritation persists. Wash clothing and clean shoes before re-use.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Most important symptoms (acute)	Contact with eyes may cause irritation. redness. Tearing. Causes skin irritation, redness, dryness with repeated or prolonged exposure. burning. Repeated exposure may cause skin dryness or cracking. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms (over-exposure)	Adverse symptoms may include the following: Eye pain, redness, and watering. Respiratory tract irritation. Coughing. Nausea or vomiting. Headache. Drowsiness/fatigue. Dizziness/vertigo. Unconsciousness. Skin irritation. Redness. Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, lungs, blood, or central nervous system.
Indication of any immediate medical attention and special treatment needed	Treat symptomatically. Treatment of overexposure should be directed at the control of symptoms and the clinical condition. NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Dry Chemical, Carbon Dioxide, Foam or Water Fog.
Unsuitable extinguishing media	Water spray, sharp water jet.
Specific hazards	Extremely Flammable Aerosol. Contents under pressure. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to

temperatures above 122°F may cause bursting. Use a water spray to cool fully closed containers. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may travel to distant and/or low-lying sources of ignition and flashback. Vapors may form explosive mixture with air.

Special protective equipment and precautions for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated in positive pressure mode. Wear full body protective clothing when fighting fires. Shut off all ignition sources. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. Cool containers exposed to flames with water until well after the fire is out. Containers should be cooled with water to prevent vapor pressure build up.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protective clothing and equipment, see section 8.

Methods and materials for containment and cleaning up

Eliminate all sources of ignition. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Clean up residue with soap and water. Do not allow material to contaminate ground water system. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Dispose of absorbent in accordance with local, state and federal regulations. Report spills as required by local and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Wear personal protective equipment. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing. Do not breathe vapors or spray mist. Store in a cool, dry, and well-ventilated place. Do not expose to temperatures exceeding 122 °F (50 °C). Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Keep out of reach of children. Keep out of the reach of children. Read label before use. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health. Incompatible with oxidizing agents. Strong reducing agents. Plastics.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	California - PELs	ACGIH OEL (TWA)	NIOSH - TWA	Mexico OEL-TWAs (VLE-PPTs)	Mexico OEL- BEIs (IBE)
Light Aliphatic Hydrocarbon Solvent	-		100 ppm TWA Skin			
Distillates, petroleum, light distillate	-					
Propane	-					
Xylenes (o-, m-, p- isomers)	100 ppm TWA 435 mg/m ³ TWA	100 ppm PEL; 435 mg/m ³ PEL	20 ppm TWA		100ppmTWA	1.5g/g creatinine
Ethyl benzene	TWA: 100 ppm TWA: 435 mg/m ³	5 ppm PEL; 22 mg/m ³ PEL	20 ppm TWA	100 ppm TWA 435 mg/m ³ TWA	20ppmTWA	0.7g/g creatinine

Appropriate engineering controls

Provide adequate ventilation to keep exposure limits below PEL.

**Individual protection measures,
such as personal protective
equipment**

Eye protection	Safety glasses/goggles.
Skin and body protection	Chemical resistant gloves. Avoid contact with skin. Chemical resistant apron.
Respiratory protection	Not required with adequate ventilation. If the exposure limits are exceeded, a NIOSH/MSHA approved respirator is recommended.
Hygiene measures	Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists. Wash hands after handling the product. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. A safety shower and eye wash station should be available for emergency use.

Canadian Province Occupational Exposure Limits

Chemical name	AB	BC	MB	NB	NL	NS	ON	PE	QC	SK
Light Aliphatic Hydrocarbon Solvent	-	-	100 ppm TWA	-	100 ppm TWA	100 ppm TWA	-	100 ppm TWA	-	-
Distillates, petroleum, light distillate	-	-	-	-	-	-	-	-	-	-
Propane	-	-	-	-	-	-	-	-	-	-
Xylenes (o-, m-, p-isomers)	100 ppm TWA 434 mg/m ³ TWA	100 ppm TWA	20 ppm TWA	100 ppm TWA	20 ppm TWA	20 ppm TWA	100 ppm TWA	20 ppm TWA	100 ppm TWAEV 434 mg/m ³ TWAEV	100 ppm TWA
Ethyl benzene	100 ppm TWA 434 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWAEV	100 ppm TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Aerosol
Color	Colorless
Odor	Xylene
Odor threshold	Not available
pH	Not available
Melting point/range °C	Not available
Melting point/range °F	Not available
Boiling point/range °C	Not available
Boiling point/range °F	Not available
Evaporation rate	No data available

Flammability (Solid, Gas)	Extremely Flammable Aerosol
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor pressure	No data available
Vapor density	No data available
Relative density	0.75 - 0.80 @ 77 °F (25 °C).
Solubility	Negligible
Partition coefficient (n-octanol/water)	Not available
Autoignition temperature °C	Not available
Autoignition temperature °F	Not available
Decomposition temperature °C	Not available
Decomposition temperature °F	Not available
Viscosity	No data available

10. STABILITY AND REACTIVITY

Reactivity	None known.
Chemical stability	This material is considered stable.
Possibility of hazardous reactions	None known.
Conditions to avoid	Avoid heat, sparks, and other sources of ignition. Avoid open flames. Incompatible materials.
Incompatible materials	Strong oxidizing agents. Strong reducing agents. Incompatible with some plastic.
Hazardous decomposition products	None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	Eyes. Dermal. Inhalation.
Symptoms	May cause eye irritation. Redness. Tearing. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard. May cause respiratory irritation. Dizziness. Headache. Nausea. Unconsciousness. Central nervous system depression. May cause irritation, localized defatting, dermatitis with prolonged or repeated contact.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	Pre-existing disorders of the skin, respiratory system and eyes will be aggravated by over exposure to this product. Contact with eyes may cause irritation, redness, tearing. Causes skin irritation, redness, dryness with repeated or prolonged exposure. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause drowsiness and dizziness. Nausea. Aspiration may cause pulmonary edema and pneumonitis. Possible

cancer causing agent and overexposure may also include damage to skin, kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, lungs, blood, or central nervous system.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Light Aliphatic Hydrocarbon Solvent	73680 ppm Rat	> 5000 mg/kg Rat >3160 mg/kg Rabbit >2000 mg/kg Rabbit	>5000 mg/kg Rat > 3160 mg/kg Rabbit > 2000 mg/kg Rabbit
Distillates, petroleum, light distillate	>12408 ppm Rat	= 5170 mg/kg Rat >3000 mg/kg Rabbit	5170 mg/kg Rat > 3000 mg/kg Rabbit
Propane	-	-	-
Xylenes (o-, m-, p- isomers)	29.08 mg/L Rat >5.04 mg/L Rat	> 1700 mg/kg (Rabbit)	= 4300 mg/kg (Rat)
Ethyl benzene	= 17.2 mg/L (Rat) 4 h	15354 mg/kg (Rabbit)	= 3500 mg/kg (Rat)

ATEmix (dermal) Not available

ATEmix (oral) Not available

ATEmix (inhalation-gas) Not available

ATEmix (inhalation-vapor) Not available

ATEmix (inhalation-dust/mist) Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA Carcinogens	NTP	Mexico
Light Aliphatic Hydrocarbon Solvent	A3	Group 3	-	-	
Distillates, petroleum, light distillate	-	-	-	-	
Propane	-	-	-	-	
Xylenes (o-, m-, p- isomers)	A4	Group 3	-	-	A4 - Not classifiable as a human carcinogen
Ethyl benzene	A3	Group 2B	X	-	A3 - Confirmed animal carcinogen

Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Light Aliphatic Hydrocarbon Solvent	-	-	ACGIH A3	-	ACGIH A3	-
Distillates, petroleum, light distillate	-	-	-	-	-	-
Propane	-	-	-	-	-	-
Xylenes (o-, m-, p- isomers)	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Ethyl benzene	-	IARC 2B	ACGIH A3	ACGIH A3	ACGIH A3	C3 Carcinogen

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects Avoid release to the environment

Chemical name	Algae/aquatic plants	Fish LC50
Light Aliphatic Hydrocarbon Solvent	-	= 8.41mg/L Oncorhynchus mykiss 96h
Distillates, petroleum, light distillate	-	-
Propane	-	-
Xylenes (o-, m-, p- isomers)	=11mg/L Pseudokirchneriella subcapitata 72h	= 13.4mg/L Pimephales promelas 96h 2.661 - 4.093mg/L Oncorhynchus mykiss 96h 13.5 - 17.3mg/L Oncorhynchus mykiss 96h 13.1 - 16.5mg/L Lepomis macrochirus 96h = 19mg/L Lepomis macrochirus 96h 7.711 - 9.591mg/L Lepomis macrochirus 96h 23.53 - 29.97mg/L Pimephales promelas 96h = 780mg/L Cyprinus carpio 96h > 780mg/L Cyprinus carpio 96h 30.26 - 40.75mg/L Poecilia reticulata 96h
Ethyl benzene	=4.6mg/L Pseudokirchneriella subcapitata 72h >438mg/L Pseudokirchneriella subcapitata 96h 2.6 - 11.3mg/L Pseudokirchneriella subcapitata 72h 1.7 - 7.6mg/L Pseudokirchneriella subcapitata 96h =11mg/L Pseudokirchneriella subcapitata 72h	11.0 - 18.0mg/L Oncorhynchus mykiss 96h 7.55 - 11mg/L Pimephales promelas 96h 9.1 - 15.6mg/L Pimephales promelas 96h = 32mg/L Lepomis macrochirus 96h = 4.2mg/L Oncorhynchus mykiss 96h = 9.6mg/L Poecilia reticulata 96h

Persistence and degradability

Product is biodegradable.

Bioaccumulation

Components in this mixture can bio-accumulate in aquatic organisms

Chemical name	CAS-No	Partition coefficient (log Kow)	Bioconcentration factor (BCF)
Light Aliphatic Hydrocarbon Solvent 64742-49-0	64742-49-0	-	-
Distillates, petroleum, light distillate 68410-97-9	68410-97-9	-	-
Propane 68476-86-8	68476-86-8	<=2.8	-
Xylenes (o-, m-, p- isomers) 1330-20-7	1330-20-7	2.77 - 3.15	0.6 - 15 dimensionless
Ethyl benzene 100-41-4	100-41-4	3.6 at 20 °C [Directive 84/449/EEC, A.8] (at pH 7.84, ECHA API)	15 dimensionless species: fish

Mobility in soil

Not available.

Other adverse effects

None known

13. DISPOSAL CONSIDERATIONS

Disposal information Dispose of all product, residues and clean-up materials in accordance with local, state, and federal regulations. Do not allow this material to drain into sewers/water supplies. Wrap container and place in trash collection. Do not puncture or incinerate. Do not reuse container.

Contaminated packaging Dispose in accordance with local, state and federal regulations.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

ID-No UN1950
 Proper shipping name Aerosols
 Hazard Class(es) 2.1
 Subsidiary Risk
 Packing group
 Special Provisions LTD QTY

TDG

ID-No UN1950
 Proper shipping name Aerosols
 Hazard Class(es) 2.1
 Packing group
 Special Provisions LTD QTY

IATA

ID-No UN1950
 Proper shipping name Aerosols, flammable
 Hazard Class(es) 2.1
 Packing group
 Special Provisions LTD QTY

IMDG/IMO

ID-No UN1950
 Proper shipping name Aerosols
 Hazard Class(es) 2.1
 Packing group
 Special Provisions LTD QTY, F-D, S-U

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Light Aliphatic Hydrocarbon Solvent	64742-49-0	-	-	-
Distillates, petroleum, light distillate	68410-97-9	-	-	-
Propane	68476-86-8	-	-	-
Xylenes (o-, m-, p- isomers)	1330-20-7	-	-	-
Ethyl benzene	100-41-4	-	-	-

Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations See information below

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Light Aliphatic Hydrocarbon Solvent	64742-49-0	X	X	X
Distillates, petroleum, light distillate	68410-97-9	-	-	-
Propane	68476-86-8	-	-	-
Xylenes (o-, m-, p- isomers)	1330-20-7	X	X	X
Ethyl benzene	100-41-4	X	X	X

California Prop. 65

Chemical name	CAS-No	California Prop. 65
Light Aliphatic Hydrocarbon Solvent	64742-49-0	-
Distillates, petroleum, light distillate	68410-97-9	-
Propane	68476-86-8	-
Xylenes (o-, m-, p- isomers)	1330-20-7	-
Ethyl benzene	100-41-4	Carcinogen

California Proposition 65

WARNING: This product can expose you to chemicals including Ethyl benzene, which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

U.S. Federal Regulations

US EPA SARA 313

See information below

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Light Aliphatic Hydrocarbon Solvent	64742-49-0	-	-
Distillates, petroleum, light distillate	68410-97-9	-	-
Propane	68476-86-8	-	-
Xylenes (o-, m-, p- isomers)	1330-20-7	100 lb 45.4 kg	1.0 %
Ethyl benzene	100-41-4	1000 lb 454 kg	0.1 %

Chemical Inventories

Chemical name	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification	DSL	NDSL	Mexico - INSQ
Light Aliphatic Hydrocarbon Solvent	X	-	X	-	Present
Distillates, petroleum, light distillate	X	-	X	-	

Chemical name	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification	DSL	NDSL	Mexico - INSQ
Propane	X	-	X	-	Present
Xylenes (o-, m-, p-isomers)	X	-	X	-	Present
Ethyl benzene	X	-	X	-	Present

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health 2
 Flammability 3
 Instability 0

HMIS

Health 2
 Flammability 3
 Physical hazards 0
 Personal protection C

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 17-Jul-2018

Revision date 05-Aug-2026

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
 ATE (Average Toxicity Estimate)
 BEI – IBE (Biological Exposure Indices for occupationally exposed personnel to chemicals)
 Biological Exposure Indices)
 DSL/NDL (Domestic Substance List/Non-Domestic Substance List)
 HMIS (Hazardous Materials Identification System)
 IARC (International Agency for Research on Cancer)
 IATA (International Air Transport Association)
 IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
 INSQ (National Inventory of Chemical Substances)
 NFPA (National Fire Protection Association)
 NTP (National Toxicology Program)
 OEL (Occupational Exposure Level)
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 PEL (Permissible Exposure Limit)
 TSCA (Toxic Substance Control Act)
 USEPA (United States Environmental Protection Agency)

VLE-PPT (Time-weighted average exposure limit value)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet